

Heater Treater Anodes

A one-piece, high temperature, flame-retardant, high-compression molded fiberglass anode mounting head. The Blue head is designed for installation in treaters fitted with 4" Schedule 80 Victaulic nipples, and the Red head is designed for installation in treaters fitted with 4" Schedule 40 Victaulic nipples.

- Designed with ribbed support skirts for easy installation, proper alignment and superior anode stability.
- Installs in standard 4-inch Sch 40 (red) or Sch 80 (blue) pipe nipple with Victaulic coupling.
- Will mount anodes of up to three (3) inch diameter and sixty (60) inch length.
- Proven service in the field since 1976.



Mount on Anode (Diameter)	Mount on Anode (Length)	Nipple Size
3 in	60 in	4 in

- 3" x 30" Aluminum Anode blank w/6" exposed 3/4" threaded core w/female coupling in bottom end
- 3" x 60" One-Piece aluminum anode blank w/6" exposed 3/4" threaded core out top end
- 3" x 30" Aluminum anode fabricated w/redhead
- 3" x 60" (1 piece) aluminum anode fabricated w/redhead
- 3" x 60" (2 piece) aluminum anode fabricated w/redhead
- 3" x 60" (1 piece) aluminum anode fabricated w/bluehead
- 3" x 60" (2 piece) aluminum anode fabricated w/bluehead