


Style CAGR Tap
conductor to the
top of a ground rod.



Style CAGT
Through conductor to the top
of a ground rod.

Ground Rod Size ¹	Conductor Size	STYLE GR			STYLE GT			
		Welder Part No. [†]	Welder Price	Weld Metal	Welder Part No. [†]	Welder Price	Weld Metal	
Nominal 1/2" (Actual .475 Dia.)	#14 to #10 Solid (use sleeve CAB-133-1H)* or #8 Solid or Stranded, or #6 Solid	CAGRT-151G	CAT	CA25	CAGTT-151G	CAT	CA32	
	6 Stranded	CAGRT-151H	CAT	CA25	CAGTT-151H	CAT	CA32	
	4 Solid	CAGRT-151K	CAT	CA25	CAGTT-151K	CAT	CA32	
	4 Stranded	CAGRT-151L	CAT	CA25	CAGTT-151L	CAT	CA32	
	2 Solid	CAGRT-151T	CAT	CA32	CAGTP-151T	CAP	CA45	
	2 Stranded	CAGRT-151V	CAT	CA32	CAGTP-151V	CAP	CA45	
	1 Stranded	CAGRP-151Y	CAP	CA45	CAGTP-151Y	CAP	CA65	
	1/0 Stranded	CAGRP-152C	CAP	CA65	CAGTP-152C	CAP	CA65	
	2/0 Stranded	CAGRP-152G	CAP	CA65	CAGTP-152G	CAP	CA65	
	Nominal 5/8" (Actual .563 Dia.)	#14 to #10 Solid (use sleeve CAB-133-1H)* or #8 Solid or Stranded, or #6 Solid	CAGRT-161G	CAT	CA32	CAGTP-161G	CAP	CA45
		6 Stranded	CAGRT-161H	CAT	CA32	CAGTP-161H	CAP	CA45
4 Solid		CAGRT-161K	CAT	CA32	CAGTP-161K	CAP	CA65	
4 Stranded		CAGRT-161L	CAT	CA32	CAGTP-161L	CAP	CA65	
2 Solid		CAGRP-161T	CAP	CA45	CAGTP-161T	CAP	CA65	
2 Stranded		CAGRP-161V	CAP	CA45	CAGTP-161V	CAP	CA65	
1 Stranded		CAGRP-161Y	CAP	CA45	CAGTP-161Y	CAP	CA65	
1/0 Stranded		CAGRP-162C	CAP	CA65	CAGTN-162C	CAN	2-CA45	
2/0 Stranded		CAGRP-162G	CAP	CA65	CAGTN-162G	CAN	2-CA45	
Nominal 3/4" (Actual .682 Dia.)		#14 to #10 Solid (use sleeve CAB-133-1H)* or #8 Solid or Stranded, or #6 Solid	CAGRT-181G	CAT	CA32	CAGTP-181G	CAP	CA45
		6 Stranded	CAGRT-181H	CAT	CA32	CAGTP-181H	CAP	CA45
	4 Solid	CAGRP-181K	CAP	CA45	CAGTP-181K	CAP	CA65	
	4 Stranded	CAGRP-181L	CAP	CA45	CAGTP-181L	CAP	CA65	
	2 Solid	CAGRP-181T	CAP	CA45	CAGTP-181T	CAP	CA65	
	2 Stranded	CAGRP-181V	CAP	CA45	CAGTP-181V	CAP	CA65	
	1 Stranded	CAGRP-181Y	CAP	CA45	CAGTP-181Y	CAP	CA65	
	1/0 Stranded	CAGRP-182C	CAP	CA65	CAGTN-182C	CAN	2-CA45	
	2/0 Stranded	CAGRP-182G	CAP	CA65	CAGTN-182G	CAN	2-CA45	

¹ For plain (unthreaded) copper-clad ground rods only. For threaded copper-clad rods or for steel rods, contact ERICO for part number.

[†] Welder Part No. includes mold frame. If mold only (less frame) is required, order - Welder Part No. - "M".

* 1 sleeve per GR connection. 2 sleeves per GT connection.