

# GMC STAPERM™ PRODUCT CATALOG 2012

“Rust Never Sleeps”

## GMC STAPERM™

### Portable Reference Electrodes

Liquid or Gelatin Filled • Rechargeable • Space  
Age Ceramic Plugs • Pointed, Round or Flat

Quality You Can Trust.

#### Features

- ❑ Color-coded for easy identification
- ❑ Infinite shelf life
- ❑ Minimum service life 20 years
- ❑ High impact ABS plastic housing
- ❑ Corrosive environment resistant
- ❑ Chloride ion trap equipped copper sulfate and zinc sulfate

#### STAPERM™ Model CU-4-PT Copper-Copper Sulfate (Cu-CuSO<sub>4</sub>) Portable Reference Electrode



- ❑ **Connection Stud:** 1/4"-20 copper.
- ❑ **Size:** 1" dia. x 8" long ABS plastic high impact yellow housing.
- ❑ **Stability:** +/-10 millivolts with 3.0 microamp load.
- ❑ **Temperature Range:** 32°F to 135°F.



#### GMC ELECTRICAL INC

2027 E. Cedar, Ontario, CA 91761 USA

Office: 909-947-6016 - Fax number: (909) 947-9430

web: [www.gmcelectrical.net](http://www.gmcelectrical.net) E-mail address: [sales@gmcelectrical.net](mailto:sales@gmcelectrical.net)

# GMC STAPERM™ PRODUCT CATALOG 2012

“Rust Never Sleeps”

## STAPERM™ Model Zn-5-PT Zinc-Zinc Sulfate (Zn-ZnSO<sub>4</sub>) Portable Reference Electrode



- ❑ **Connection Stud:** 1/4"-20 copper.
- ❑ **Size:** 1" dia. x 8" long ABS plastic high impact red housing.
- ❑ **Stability:** +/-10 millivolts with 3.0 microamp load.
- ❑ **Temperature Range:** 32°F to 135°F.

## STAPERM™ Model AG-4-PT Silver-Silver Chloride (Ag-AgCl) Portable Reference Electrode



- ❑ **Connection Stud:** 1/4"-20 copper.
- ❑ **Size:** 1" dia. x 8" long ABS plastic high impact red housing.
- ❑ **Stability:** +/-10 millivolts with 3.0 microamp load.
- ❑ **Temperature Range:** 32°F to 135°F.



### GMC ELECTRICAL INC

2027 E. Cedar, Ontario, CA 91761 USA

Office: 909-947-6016 - Fax number: (909) 947-9430

web: [www.gmcelectrical.net](http://www.gmcelectrical.net) E-mail address: [sales@gmcelectrical.net](mailto:sales@gmcelectrical.net)