



Fisher TW-6 Pipe & Cable Locator

The TW-6 Pipe & Cable locator finds underground pipes, cables, manhole covers, vaults, valve boxes and other metallic objects

AFFORDABLE, TOUGH AND SIMPLE TO USE.

- The industry standard
- Unlike other units that use a separate transmitter and receiver, the TW-6, when mounted on the handle, can conduct “blind” searches of an area to locate an underground pipe or cable where the starting point is unknown
- Noise cancelling circuitry eliminates power line interference

OPTIONAL ACCESSORIES

- Tracer Probe
- Coupling Clamp
- 3 pc Handle Kit
- Hard Carrying Case
- Sonde
- Stereo Headphones
- Fisher Phones
- Ground Rod Harness Assembly Included



RECEIVER

- Operating Frequency: 81.92 kHz + .005%
- Batteries: 8 each AA (NEDA 15)
- Weight: 3 lbs. (1.36 kg)
- Sensitivity: Normal: 400 uV typical High: 8 uV typical
- Signal-to-noise Ratio: 110 dB
- Headset Impedance: 600 ohms (mono) 8 ohms (stereo)
- Dimensions: 11 1/2" x 9" x 3" (29 x 23 x 7.6 cm)
- Operating Temperature: -10°F to +120°, (-23°C to +48°C) depending on batteries used
- Total Weight: 5.5 lbs. (2.5 kg) - (without handle accessory, ground plate assembly and op manual)
- Total Shipping Weight: 6.75 lbs. (3 kg) - (including only ground plate assembly and operating manual)



TRANSMITTER

- Operating Frequency: 81.92 kHz + .005%
- Batteries: 8 each AA (NEDA 15)
- Weight: 2.5 lbs. (1.1 kg)
- Dimensions: 11 1/2" x 9" x 3" (29 x 23 x 7.6 cm)
- Operating Temperature: -10°F to +120°, (-23°C to +48°C)

