INKER & MASOR


MODEL CPV-2

CATHODIC PROTECTION


VOLTMETERS

MODEL CPV-2

10 MΩ Impedance Swing Needle Meter "AA" Batteries Filter AC Interference 0 - 2 volts DC scale Color Code display



- Anode to Structure
 Structure to Structure
- Insulated Flanges
 Structure to Earth



Both instruments come complete with:

- Instrument with battery
- Heavy Duty coiled cables with clamps
- Model 6-A Half Cell electrode
- · Convenient carrying case

MODEL CPV-4


11 M Ω Impedance

LCD Digital Meter
9 volt Battery
Filter AC Interference
2 volt and 20 volt DC scale
Meter displays + (POS) or - (NEG) reads

Distributed by

MESA PRODUCTS INC. 4445 S. 74th E. Ave. Tulsa, OK 74145 Phone: 918-627-3188

1-888-800-MESA



Use for potential reads:

- Anode to Structure
- Insulated Flanges
- Structure to Structure
- Structure to Earth





Tinker & Rasor Cu-Cu/SO4 half cell reference electrodes screw directly into the back of the meters!

Combine with optional extension handle for one hand operation.

www.teststations.com

www.detectron.com



www.tinker-rasor.com

Info@tinker-rasor.com

Tinker & Rasor quality is found in our products, our people and our customer service.



> VOLTME



PRODUCT DATA SHEET

MODEL CPV-2

Features:

- •10M Ω Impedance
- ± 3% of full scale
- 2v DC scale
- · "AA" Batteries
- · Color coded display

Construction:

Strong aluminum square tubing Integrated circuits Rugged analog meter

Applications:

- CP Potentials
- · Structure to Earth
- Insulated Flanges

Dimensions:

3" Square (76mm)

MODEL CPV-4

Features:

- 11MW Impedance
- Digital LCD display (shows + or -)
- ±0.1% + last digit accuracy
- Dual scale, 0-.999v, 0-19.99v
- · Includes reference cell and cables

Construction:

Durable die-cast aluminum case Powder coat finish Integrated circuits

Applications:

- CP Potentials
- Structure to Earth
- Structure to Structure

Dimensions:

4-5/8" x 3-5/8" x 2-3/16" (117mm x 92mm x 59mm)

DELIVERY: Immediately from STOCK

EX-Works San Bernardino, CA USA

SERVICE: 24-hour Turn-Around

TERMS: Net30 Days, on approval of credit

WARRANTY: 90 Days, parts and labor



AVAILABLE FROM STOCK