



## Fill-Putty™



### Description:

Fill-Putty™ is an anticorrosive moldable filler material used to even the contours of irregular fittings and surfaces. Once applied, it is overwrapped with Trenton's Wax-Tapes.

### Application:

Brush or wipe the surfaces clean of dirt, loose rust or old coating and other foreign materials. Apply Fill-Putty directly by hand, working the material onto the metal surface ensuring that the putty is "wetting" and adhering to the surface.

Continue applying the material in and around the voids, contours and crevices so as to build up an even surface all around the fitting or structure.

Then overwrap the entire application with Trenton's Wax-Tapes®.

### Packaging:

2 inch diameter by 13 inch long links  
20 links per case  
40 lbs. per case

### Specifications:

Specific Gravity .....	1.15
Density .....	24 cu. in. per lb.
Application Temperature .....	40°F to 200°F
Service Temperature.....	200°F Maximum
Flash Point.....	350°F Minimum
Pour Point .....	240°F



**Corporate Office:**  
7700 Jackson Road  
Ann Arbor, MI 48103 USA  
(734) 424-3600  
Fax: (734) 426-5882  
trenton@trentoncorp.com

**Export/Houston Office:**  
1880 S. Dairy Ashford Rd.  
Suite #697  
Houston, Texas 77077 USA  
(281) 556-1000  
Fax: (281) 556-1122  
tweber@trentoncorp.com

**European Office:**  
8, rue de Berri  
Paris, France 75008  
+33 (0) 1 42 99 95 78  
Fax: +33 (0) 1 42 99 95 79  
europe@trentoncorp.com

**[www.trentoncorp.com](http://www.trentoncorp.com)**