



**TECHNICAL DATA SHEET VISCOTAQ EZ WRAP**

**Description:** VISCOTAQ EZ Wrap is a versatile and economical product intended for a wide range of structural applications, where water leaks and corrosion are a problem. VISCOTAQ EZ Wrap provides for a quick and economical method of installation with excellent sealing and adhesion properties. This material is strengthened by a fiber mesh that is imbedded in the middle of the material and has a white polyester non-woven fiber top layer that allows for the immediate painting or coating after installation. VISCOTAQ EZ Wrap has immediate adhesion to steel, PE, PP, epoxy, polyurethane, PVC, etc. without roughening. There is no cure or hardening time required. VISCOTAQ EZ Wrap is storage stable (dry/cool) with an unlimited shelf life.

**Applications:** VISCOTAQ EZ WRAP is engineered for use in many water leak and corrosion prevention applications, offering long-term performance in commercial, residential, telecommunications, utilities, transportation, electrical, water, wastewater, agricultural, and industrial as well as others. The primary applications are soil to air transitions, pipe coating rehabilitation, bridge crossings, encapsulation of lead base paint, metal roof seams, flashings, residential and commercial roofing, EPM roofing, pipe and cable entries, holes and voids, cracks, storage tanks, industrial pools, swimming pools, manholes, basements, floors, cable joints and repairs, and etc. VISCOTAQ EZ WRAP is also used in conjunction with other VISCOTAQ Products such as VISCOTAQ Sealant, Viscoshield.

**PROPERTIES:**

<b>Product Name:</b>	<b>VISCOTAQ EZ WRAP</b>
Color	Gray
Odor	None
Density	1.4
Perm rating	<0.0050 g/m <sup>2</sup> /24h/cc Hg
Water Intake	<0.4% (compound)
Spec Electric Resistance	>1012 ohm cm
Viscosity	Viscous Elastic solid (putty like)
pH	Neutral
Shelf Life	Unlimited
Max. Operating Temp.	158 F, melting point 265 F
Min. Operating Temp.	-50 F
Adheres to Wet Surface	No
Min. Temp. (no cracks)	-22 F
Application	Above and below grade applications

**Performance:** VISCOTAQ EZ WRAP is a permanent solution to a variety of water and corrosion problems. VISCOTAQ EZ WRAP has been highly successful in solving water leakage and corrosion problems in numerous markets.

**Specifications:** The VISCOTAQ EZ WRAP is a mastic-like material designed with synthetic properties that will adhere to almost any surface without a primer. The VISCOTAQ EZ WRAP comes in rolls and can be painted and/or coated. VISCOTAQ EZ WRAP is patent pending.

**Application Instructions:**

- Clean the application with a dry cloth. Remove as much of the loose material on the area as you can.
- Peel off the clear release liner from the roll of the EZ Wrap and align the EZ Wrap on the area you are applying it to.
- Use a Steel Seam Roller to apply the press the EZ Wrap to the surface.
- During cold weather, preheat the surface with for instance a hot air gun. When not allowed, preheat the rolls by carrying them inside the cabin of the car.

**Maintenance:** INSPECTION: peel test: peel away from the side of the EZ Wrap to see if full adhesion has occurred (within half an hour to an hour). If not full adhesion has occurred, press down with a steam roller and/or heat the area with a hot air blower or heat gun.

**Technical Service:** VISCOTAQ provides technical support to assist in product selection and appropriate installation design. Technical information is available upon request.

**Precautionary Information:** No unusual hazards are known or expected. Observe normal safety procedures during installation. MSDS Sheets are available upon request.

**Availability:** VISCOTAQ EZ WRAP is available from authorized VISCOTAQ distributors nationwide. Contact VISCOTAQ for the names and locations of the nearest sales representative or distributors.

**Important Notice:** All statements, technical information, and recommendations contained herein are based upon testing believed to be reliable, but the accuracy and completeness thereof is not guaranteed.

**Warranty:** VISCOTAQ Products manufactures its goods in a manner to be free of defects. Should any defect occur in its goods (within one year), VISCOTAQ, upon prompt notification, will at its option, exchange or repair the goods.