

# Model CT231A

## Amp Clamp Accessory



### CT231A Specifications (at 23 °C ± 5 °C, < 75 % R.H. non-condensing)

| AC Current (50-1000 Hz) |  |
|-------------------------|--|
| Range                   | 1 to 200 A   |
| Accuracy                | Meter impedance (Load = 1 Ω max.):<br>1 A to 40 A: ± (3 % rdg + 0.5 A)<br>40 A to 200 A: ± (2 % rdg + 0.5 A) |
|                         | Meter impedance (Load = 10 Ω max.):<br>1 to 200 A: ± (3.0 % rdg + 0.15 A)                                    |
| Division Ratio          | 1000 to 1  |
| Output                  | 1 A at jaws = 1 mA to meter  |
| Overload Protection     |  |
| Max Operating Voltage   | 600 V rms  |



### General Specifications

**Max Conductor Diameter:** 20 mm (0.78"); **Dimensions:** 30 x 51 x 139 mm (1.2" x 2.0" x 5.5"); **Lead Length:** 1.5 m (59"); **Operating Temperature:** - 10 °C to + 50 °C; **Dimensions (HxWxD):** 30 x 51 x 139 mm (1.2" x 2.0" x 5.5"); **Weight:** 260 grams (9 oz); **Included Accessories:** Operators manual

| Features                                       |
|--|
| Permanently Attached Leads; Warranty: One-year |
| Optional Accessories                           |
| VC30 Vinyl Case                                |

For additional accessories, see the Accessories Compatibility Guide at [www.metermantesttools.com](http://www.metermantesttools.com)



- AC current clamp, 200 A
- CAT III 600 V rated

## **Model CT231A**

### **Amp Clamp Accessory**

**Meterman.**  
**The right tool for the job.<sup>™</sup>**

**Meterman Test Tools**  
website: [www.metermantesttools.com](http://www.metermantesttools.com)  
email: [info@metermantesttools.com](mailto:info@metermantesttools.com)

6920 Seaway Blvd.  
Everett, WA 98203  
fax: 425-446-4882  
tel: 877-596-2680

Meterman Test Tools Europe  
P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands